

AURORA I Genn IV

New Generation Aurora series

The new generation G2G Aurora I GenIV LED modules are innovatively designed as an optimal solution for outdoor and indoor lighting. Ideal for channel letters, illuminated light boxes and decorative architectural lighting.



cUL[®]us **IP68**
E344189

RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

LED MODULE SPECIFICATIONS

Working mode	Constant Current Technology (CCT)	Fastening	3M VHB double face tape and mechanical mounting options.
Max Mods (Series)	Full 70W load	Optical Structure	UV or IR Protected
Viewing Angle	120°	Packaging	100 modules per tray, 5 trays per case
CT	7500K	Protection Grade	IP68 wet-Location
CRI	>70	Certifications	UL and cUL Recognized
LEDs Per Module	3	Warranty	5 Year
Operating Temp	-40° to +60°C		
LED Module Dimension	2.56"L x 0.78"W x 0.39"H		

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora I Gen IV	12VDC	0.70W/Module	58mA	3	7500K	195 Lm/Ft	84Modules/28Ft	120°

LED MODULE DIMENSIONS

